



TECHNICAL DATA SHEET

LPTAE

Description	Metal ramp trim; DIY-Set; self adhesive
Reference	LPTAE 800-SK LPTAE 1400-SK LPTAE 2200-SK
Material	Aluminium
Surface	Anodised
Color	Silver
Length	270 cm
Height (H)	6-10 mm 12-16 mm 20-22 mm
Width (A)	43 mm 43 mm 55 mm
Width (B)	21 mm
Weight	0,182 kg/m 0,224 kg/m 0,256 kg/m
Picture	<p>The diagram illustrates the ramp trim's profile. It shows a side view of the trim with a vertical height 'H' indicated by a dimension line. The base width 'A' is shown as a horizontal line at the bottom. The top width 'B' is indicated by a horizontal line at the top edge of the trim's profile. The trim itself is depicted with a shaded, stepped cross-section.</p>



DURAL GmbH – Südring 11 – D-56412 Ruppach-Goldhausen Tel. +49 (0) 2602/9261-0 Fax +49 (0) 2602/9261-50 info@dural.com

DURAL UK Ltd. – Unit 6a, Wakefield Business Centre, Denby Dale Road, Wakefield, West Yorkshire, WF2 7AZ Tel. 01924 360110 sales@dural.co.uk

DURAL USA, Inc. – 711 N Varnell Rd. – Tunnel Hill, GA 30755 Tel. 800 278 1956 Fax 706 519 0395 mail@dural.com

www.dural.com



TECHNICAL DATA SHEET



Anodised aluminium

Anodisation is a special finish that improves the look of aluminium profiles. The anodised surface is susceptible to scratches and may become faded, particularly due to the effect of alkaline building products. Contact with fresh cement can cause surface corrosion. Adhesive and grout should always be removed immediately from all visible surfaces using plenty of water. Once oxidation marks have been allowed to appear, it is practically impossible to remove them. Use only cleaning agents with neutral pH that do not scour. Make sure that good room ventilation is provided, especially when joining in combination with high-gloss anodised profiles, in order to achieve fast curing of the joints. This also reduces the alkaline potential of the cement (lowers the pH), thereby preventing any possible damage to the anodised surface.

Note

The suitability for use in terms of mechanical and chemical resistance must always be checked in each individual case. When installing and grouting our metal profiles, the adhesive and grouting materials must be removed immediately with clean water and a soft sponge to prevent damage due to corrosion of the profile. Do not use acidic (e.g. cement fog remover) or alkaline cleaning agents in combination with all metal profiles. Clean with clean water and wipe with a dry linen cloth.

LP-Trans can also be installed on tiles. For installation with tiles, the surface must be smooth and free from contaminations, such as oil, dust, fat etc. to make sure that the glue can bond to the tile.